

产品选型表

HTT850	分体式温湿度变送器									
	量程	(湿度默认 0-100%)								
	01	0-50℃								
	02	-10-60℃								
	03	-20-60℃								
	04	-40-80℃								
	05	-40-120℃								
	DR	定制								
	信号输出	信号输出								
		A	电流型 4-20 mA 三线制							
		V0	电压型 0-5 V DC 三线制							
		V1	电压型 0-10 V DC 三线制							
		RS	RS485 通讯接口 (标准 Modbus-RTU 协议) 四线制							
		DY	信号定制							
		湿度精度	湿度精度							
			2	±2%RH (25℃ 10-90%RH)						
			3	±3%RH (25℃ 10-90%RH)						
			5	±5%RH (25℃ 10-90%RH)						
		显示	显示							
			D	LED 显示						
			N	无显示						
		代号	代号	分体引线长度						
			1m	1 米						
			5m	5 米						
			10m	10 米						
			DL	长度定制						
			代码	代码	固定形式					
				20M	M20*1.5					
				27M	M27*2					
				DM	定制					
			代码	代码	探头长度					
				50	不锈钢 插深长度 50mm					
				100	不锈钢 插深长度 100mm					
				DZ	不锈钢 探头长度定制					
			代号	代号	耐压					
				NA	无耐压					
				A	1MPa					
				B	3MPa					
				C	5MPa					

例：HT850-01. A. 3. D. 1m. 20M. 50. NA (HT850型分体式温湿度变送器 量程：0-50℃ 0-100% RH, 输出三线制4-20mA, 精度±0.5℃ ±3%RH LED显示 分体引线1米 螺纹M20*1.5 探头长度50mm 无耐压)