

选型表

Selection table

TS600	偶头温度传感器（中低温-200~500℃）									
	代码	偶头类型								
	BR	BR 头								
	BK	BK 头								
		代码	量程范围							
		PT*	-200~500℃（电阻输出选型：PT100A PT100B PT1000A PT1000B）							
		01	0~100℃							
		02	-50~50℃							
		03	0~450℃							
		DR	定制量程							
		代码	输出信号							
		A	4~20mA 二线制							
		R	阻值信号（仅限PT*选型 默认三线制）							
		DY	定制信号							
		代码	插深（默认含螺纹）							
		L50	50mm							
		L100	100mm							
		L200	200mm							
		LX	其他长度							
		代码	冷端							
		H0	无冷端							
		H50	50mm							
		H100	100mm							
		H150	150mm							
		代码	杆径							
		D6	6mm							
		D8	8mm							
		DX	定制							
		代码	护管材质							
		04	304 不锈钢							
		16	316 不锈钢							
		DC	定制材质							
		代码	螺纹							
		20M	M20*1.5 外螺纹							
		27M	M27*2 外螺纹							
		4G	G1/2 外螺纹							
		DM	定制							
		代码	精度（带变送）							
		H	±0.2%F.S							
		L	±0.5%F.S							

例：TS600.BR.01.A.L100.H0.D6.04.20M.L（TS600系列偶头温度传感器 BR偶头
量程：0~100℃ 插深100mm 杆径6mm 保护管材质304不锈钢 螺纹M20*1.5 精度：±0.5%F.S）

选型表

Selection table

TS610		偶头温度传感器（高温0~1600℃）			
	代码	量程范围			
	01	0~800℃			
	02	0~1000℃			
	03	0~1200℃			
	04	0~1600℃			
	DT	定制量程			
	代码	输出信号			
	A	4-20mA 二线制			
	V1	0-5V 三线制			
	V2	0-10V 三线制			
	RS	RS485			
	M	热电偶 MV 信号			
	代码	插深（默认含螺纹）			
	L50	50mm			
	L100	100mm			
	L200	200mm			
	LX	其他长度			
	代码	冷端			
	H0	无冷端			
	H50	50mm			
	H100	100mm			
	H150	150mm			
	代码	杆径			
	D6	6mm			
	D8	8mm			
	DX	定制			
	代码	护管材质			
	04	304 不锈钢			
	16	316 不锈钢			
	DC	定制材质			
	代码	螺纹			
	20M	M20*1.5 外螺纹			
	27M	M27*2 外螺纹			
	4G	G1/2 外螺纹			
	DM	定制			
	代码	精度（带变送）			
	H	±0.2%F.S			
	L	±0.5%F.S			

例：TS610.02.A.L100.D6.H100.04.20M.L （TS610系列偶头温度传感器 量程：0-1000℃
输出：4-20mA 插深100mm 杆径6mm 保护管材质304不锈钢 螺纹M20*1.5 精度：±0.5%F.S）