

选型表

Selection table

TS700	小 B 型头温度传感器（中低温-200~500 ℃）							
	代码	芯片						
	PT100A	-50~300℃	精度：0.15+0.002 t					
	PT100B	-70~500℃	精度：0.3+0.05 t					
	PT1000A	-50~300℃	精度：0.15+0.002 t					
	PT1000B	-70~500℃	精度：0.3+0.05 t					
	PT100BL	-196~150℃	精度：0.3+0.05 t					
		代码	插深（默认含螺纹）					
		L30	30mm					
		L50	50mm					
		L100	100mm					
		L150	150mm					
		LX	定制					
			代码	冷端				
			H0	无冷端				
			H50	50mm				
			代码	杆径				
			D6	6mm				
			D8	8mm				
			DX	定制				
			代码	护管材质				
			04	304 不锈钢				
			16	316 不锈钢				
			DC	定制材质				
			代码	螺纹				
			20M	M20*1.5 外螺纹				
			27M	M27*2 外螺纹				
			4G	G1/2 外螺纹				
			DM	定制				
			代码	线制				
			2W	二线制				
			3W	三线制				
			4W	四线制				
TS700	PT100A	L50	H0	D6	04	20M	3W	

例：TS700.PT100A.L50.H0.D6.04.20M.3W （TS700系列小B型头温度传感器 芯片PT100
精度：A级 插深50mm 杆径6mm 保护管材质304不锈钢 螺纹M20*1.5 三线制

选型表

Selection table

TS710	小 B 型头温度传感器（高温0~1600℃）							
	代码	芯片						
	K	K 型热电偶 0~1200℃ 精度：II 级						
	T	T 型热电偶 -200~350℃ 精度：II 级						
	E	E 型热电偶 0~900℃ 精度：II 级						
	S	S 型热电偶 0~1600℃ 精度：II 级						
	B	B 型热电偶 0~1700℃ 精度：II 级						
		代码	插深（默认含螺纹）					
		L30	30mm					
		L50	50mm					
		L100	100mm					
		L150	150mm					
		LX	定制					
		代码	冷端					
		H0	无冷端					
		H50	50mm					
		H100	100mm					
		H150	150mm					
		代码	杆径					
		D6	6mm					
		D8	8mm					
		DX	定制					
		代码	护管材质					
		04	304 不锈钢					
		16	316 不锈钢					
		DC	定制材质					
		代码	螺纹					
		20M	M20*1.5 外螺纹					
		27M	M27*2 外螺纹					
		4G	G1/2 外螺纹					
		DM	定制					
TS710	PT100A	L50	H0	D6	04	20M	3W	

例：TS710. K. L50. H100. D6. 04. 20M （TS710系列小B型头温度传感器 K型热电偶 插深50mm 杆径6mm 保护管材质304不锈钢 螺纹M20*1.5 三线制）