

选型表

Selection table

TS900	防护型温度传感器（中低温-200~500 ℃）													
	代码	量程范围												
	PT*	-200~500℃（电阻输出选型：PT100A PT100B PT1000A PT1000B）												
	01	0~100℃												
	02	-50-150℃												
	03	0~450℃												
	DR	定制量程												
		代码	输出信号											
		A	4-20mA 二线制											
		R	阻值信号（仅限PT*选型 默认三线制）											
		DY	定制信号											
			代码	插深（默认含螺纹）										
			L50	50mm										
			L100	100mm										
			L200	200mm										
			LX	其他长度										
				代码	冷端									
				H0	无冷端									
				H50	50mm									
				H100	100mm									
				H150	150mm									
					代码	杆径								
					D6	6mm								
		D8			8mm									
		DX			定制									
					代码	护管材质								
			04		304 不锈钢									
			16		316 不锈钢									
			DC		定制材质									
				代码	螺纹									
				20M	M20*1.5 外螺纹									
				27M	M27*2 外螺纹									
				4G	G1/2 外螺纹									
		DM		定制										
				代码	精度（带变送）									
				H	±0.2%F.S									
				L	±0.5%F.S									
					代码	防爆								
					d	隔爆Exd II CT6								
			N		无防爆									
					代码	显示								
				D	LED显示									
		N		无显示										
TS900	01	A	L100	H50	D6	04	20M	L	Y	N				

例：TS900.01.A.L100.H50.D6.04.20M.L.Y.N（TS900系列防护型温度传感器 量程：0~100℃ 插深100mm 冷端50mm 杆径6mm 保护管材质304不锈钢 螺纹M20*1.5 精度：0.5%F.S 隔爆 无显示）

选型表

Selection table

TS910	防护型温度传感器（高温0-1600 ℃）													
	代码	量程范围												
	01	0~800℃												
	02	0~1000℃												
	03	0~1200℃												
	04	0~1600℃												
	DT	定制量程												
		代码	输出信号											
		A	4-20mA 二线制											
		R	阻值信号（仅限PT*选型 默认三线制）											
		DY	定制信号											
			代码	插深（默认含螺纹）										
			L50	50mm										
			L100	100mm										
			L200	200mm										
			LX	其他长度										
				代码	冷端									
				H0	无冷端									
				H50	50mm									
				H100	100mm									
				H150	150mm									
					代码	杆径								
					D6	6mm								
					D8	8mm								
					DX	定制								
					代码	护管材质								
					04	304 不锈钢								
					16	316 不锈钢								
					DC	定制材质								
						代码	螺纹							
						20M	M20*1.5 外螺纹							
		27M	M27*2 外螺纹											
		4G	G1/2 外螺纹											
		DM	定制											
			代码	精度（带变送）										
			H	±0.2%F.S										
			L	±0.5%F.S										
				代码	防爆									
				Y	隔爆Exd II CT6									
				N	无防爆									
					代码	显示								
		D			LED显示									
		N			无显示									
TS910														

例：TS910.01.A.L100.H50.D6.04.20M.L.Y.N（TS900系列防护型温度传感器 量程：0-100℃ 插深100mm 冷端50mm 杆径6mm 保护管材质304不锈钢 螺纹M20*1.5 精度：0.5%F.S 隔爆 无显示）